













Connection Cable S4 with female straight plug

Designation	Connection Cable S4/3		Connection Cable S4/4		Connection Cable S4/5	
Application	3-pole female, for units with plug S4		4-pole female, for units with plug S4		5-pole female, for units with plug S4	
						
						
Design	Moulded cable		Moulded cable		Moulded cable	
Cable material	PVC		PVC		PVC	
Wire diameter	3 x 0,25 mm ²		4 x 0,25 mm ²		5 x 0,34 mm ²	
Protection class	IP 67/68		IP 67/68		IP 67/68	
Ambient temperature	-25 ... +80 °C		-25 ... +80 °C		-25 ... +80 °C	
	Type	Art.-No.	Type	Art.-No.	Type	Art.-No.
Cable length of 2 m	ST043/3-2	9850I			ST043/5-2	9850C
Cable length of 5 m	ST043/3-5	9850X	ST043/4-5	9841T	ST043/5-5	9850D
Cable length of 10 m	ST043/3-10	9850Y	ST043/4-10	9850J		
Cable length of 15 m						

Designation	Connection Cable S4/3 H		Connection Cable S4/4 H		Connection Cable S4/5 H	
Application	3-pole female, for units with plug S4		4-pole female, for units with plug S4		5-pole female, for units with plug S4	
						
						
Design	Moulded cable		Moulded cable		Moulded cable	
Cable material	PP		PP		PP	
Wire diameter	3 x 0,34 mm ²		4 x 0,34 mm ²		5 x 0,34 mm ²	
Protection class	IP 69		IP 69		IP 69	
Ambient temperature	-40 ... +105 °C		-40 ... +105 °C		-40 ... +105	
	Type	Art.-No.	Type	Art.-No.	Type	Art.-No.
Cable length of 2 m	ST 043/3-2H	9850P	ST043/4-2H	9844R	ST043/5-2H	9850R
Cable length of 5 m	ST 043/3-5H	9850Q	ST043/4-5H	9842P	ST043/5-5H	9844V
Cable length of 10 m	ST 043/3-10H	9850W	ST043/4-10H	9844O	ST043/5-10H	9844Z
Cable length of 15 m			ST043/4-15H	9844P		
Cable length of 25 m			ST043/4-25H	9844Q		