

- 1 optic
- For integration in roller conveyor
- Slidable mounting flange
- Integrated air cooling and air purging
- stainless steel

**Product Characteristics**

Type	OIL 2001
Art.-No.	6442F
Suitable evaluation unit	OXLF 1L41.3A GVK
Application	Material detection of hot objects on roller conveyors


Technical Data

Number of optics	1
Protective tube length L	2000 mm (overall length 2500 mm)
Air consumption	approx. 85 l/min (1,5 bar)
Fiber optic length	5 m
Matching mounting flange	DIN 2576 DN125 PN10
Ambient temperature	-40 ... +250 °C (without cooling)
Protection class	IP 42
Housing material	Stainless steel
Weight	approx. 30 kg

Optic

Distance	Spot diameter
0,3 m	14 mm
0,5 m	16 mm
1 m	20 mm
1,5 m	30 mm

Dimension (mm)



Accessories (in scope of supply)

	Type	Art.-No.
optic	DAK 340	6914P
fiber optic cable 5 m length	LLKD 5	6441C
1 m cable protection hose	KSS HCX 3/4"	9862F
Protection hose gland	KSV M25A	9860R

Accessories (not in scope of supply)

	Type	Art.-No.
Protective tube to improve the air purging on the optics	OL 45	6914W

Further information

	Document
-	-

Mounting

