
Inductive proximity switch
IKZ 475.38 G

- Brass nickel-plated housing PG 36
- Rated operating distance (S_n) 25 mm
- PNP normally open + normally closed




Product Characteristics

Type	**IKZ 475.38 G**
Connection	**Art.-No.**
2 m PVC cable	2409J
5 m PVC cable	2409J-5
10 m PVC cable	2409J-10
15 m PVC cable	2409J-15
20 m PVC cable	2409J-20
Application	Non-contact detection of metallic objects


Technical Data

Rated operating distance (S_n)	25 mm
Target steel St37, 1 mm thick	75 x 75 mm
Operating distance adjustable	no
Switching hysteresis (H)	1 - 15 %
Location at metal	conditionally flush (free zone 5 mm)
Supply voltage (U_B)	10 - 55 V DC
Ripple voltage	max. 15 %
Output	PNP normally open + normally closed
Continuous current	0 - 400 mA
Short-circuit protection	yes, pulsing
No-load current (I_0)	< 10 mA
Voltage drop (U_d)	< 2 V
Operating frequency (f)	100 Hz
Ambient temperature	-25 ... +70 °C
Protection class	IP 67
Housing material	brass, nickel plated
Functional display	LED

Connection



Dimension (mm)



Accessories (in scope of supply)

	Type	Art.-No.
Brass nickel-plated nut PG 36 (2 pieces)	HL 4	9849A

Accessories (**not** in scope of supply)

	Type	Art.-No.
-	-	-

Further information

	Document
Operating manual	BDA_IK_D_E